

Selection Guide

Tough- & Standard Fahrzeugmonitore

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

www.delta-components.de

www.automotive-computing.com

PDF Online Selection Guide
Stand vom 13.05.2024 - 15:57:38

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.



7" DeltaToughMon Type 1



7" DeltaToughMon Type 2



7" DeltaToughMon Type 3

LCD Size	7"	7"	7"
Active Area	-	-	-
Aspect Ratio	16:9	16:9	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WSVGA (1.024x600)	WSVGA (1.024x600)	WSVGA (1.024x600)
Display Colors	-	-	-
Brightness	600 cd/m²	1.000 cd/m²	1.000 cd/m²
Contrast Ratio	700:1	700:1	700:1
Response Time	10 / 15 ms (Tr / Tf)	10 / 15 ms (Tr / Tf)	10 / 15 ms (Tr / Tf)
Viewing Angle	150° / 145° (H / V)	150° / 145° (H / V)	150° / 145° (H / V)
Anti Reflection Glass	x	x	x
Sunlight Readable	-	x	x
Gapless Optical Bonding	-	-	-
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	Projected Capacitive Multi-Touch	Projected Capacitive Multi-Touch	Projected Capacitive Multi-Touch
Cooling System	-	-	-
Mounting System	50 x 50 mm VESA, Copper Monitor Stand incl. Stand	50 x 50 mm VESA, Copper Monitor Stand incl. Stand	50 x 50 mm VESA, Copper Monitor Stand incl. Stand
Graphic Interface	VGA/CRT, DVI, HDMI	VGA/CRT, DVI, HDMI	VGA/CRT, DVI, HDMI
Interface COM	-	-	-
Interface USB	USB-Touch USB	USB-Touch USB	USB-Touch USB
Camera	-	-	-
Video Input	-	-	-
Reverse camera input	-	-	-
Audio	-	-	-
Speakers	-	-	-
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	10 to 35VDC	10 to 35VDC	10 to 35VDC
Input Current	< 10W	< 10W	< 10W
Operating Temperature	-20°C to 70°C	-20°C to 70°C	-20°C to 70°C
Storage Temperature	-30°C to 80°C	-30°C to 80°C	-30°C to 80°C
Relative Humidity	-	-	-
Protection	-	-	IK08 Impact Protection
Certification	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs
Dimensions	196 x 121,5 x 35 mm (W x H x D)	196 x 121,5 x 35 mm (W x H x D)	196 x 121,5 x 35 mm (W x H x D)
Weight	0,7 Kg	0,7 Kg	0,7 Kg
Material	-	-	-
Typ. Application	Industrial, Automotive, Digital Signage	Industrial, Automotive, Digital Signage	Industrial, Automotive, Digital Signage

Selection Guide Tough- & Standard Fahrzeugmonitore



7" DeltaToughMon Type 1



7" DeltaToughMon Type 2



7" DeltaToughMon Type 3

Bestellinformation

Artikel-Nr. DMTX3000

7" DeltaToughMon Type 1, 1.024x600 w/ PCT,
LCD Monitor, 600cd/m², VGA, DVI, HDMI, AV

Artikel-Nr. DMTX3001

7" DeltaToughMon Type 2, 1.024x600 w/ PCT,
LCD Monitor, 1.000cd/m², VGA, DVI, HDMI, AV

Artikel-Nr. DMTX3002

7" DeltaToughMon Type 3, 1.024x600 w/ PCT,
Optical Bonding, LCD Monitor, 1.000cd/m², VGA,
DVI, HDMI, AV, IK08

PDF Online Selection Guide
Stand vom 13.05.2024 - 15:57:38

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.



7" DeltaToughMon Type 4



7" DeltaToughMon Type 5



7" DeltaToughMon Type 6

LCD Size	7"	7"	7"
Active Area	-	-	-
Aspect Ratio	16:9	16:9	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WSVGA (1.024x600)	WSVGA (1.024x600)	WSVGA (1.024x600)
Display Colors	-	-	-
Brightness	1.000 cd/m²	600 cd/m²	600 cd/m²
Contrast Ratio	700:1	700:1	700:1
Response Time	10 / 15 ms (Tr / Tf)	10/15 ms (Tr/Tf)	10 / 15 ms (Tr / Tf)
Viewing Angle	150° / 145° (H / V)	150/145 (H/V)	150° / 145° (H / V)
Anti Reflection Glass	x	-	-
Sunlight Readable	x	x	-
Gapless Optical Bonding	-	-	-
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	-	-	Projected Capacitive Multi-Touch
Cooling System	-	-	-
Mounting System	50 x 50 mm VESA, Optional Stand	50x50 mm VESA, Copper Monitor Stand incl. Stand	50x50mm VESA, Copper Monitor Stand incl. Stand
Graphic Interface	VGA/CRT, DVI, HDMI	VGA/CRT, DVI, HDMI	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI, HDMI
Interface COM	-	-	-
Interface USB	USB-Touch USB	-	USB-Touch USB
Camera	-	-	-
Video Input	-	-	-
Reverse camera input	-	-	-
Audio	-	3x Audio In	3x Audio In
Speakers	-	built-In Speakers	built-In Speakers
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	10 to 35VDC	10 to 35VDC	10 to 35VDC
Input Current	< 20W	< 10W	< 10W
Operating Temperature	-20°C to 70°C	-20°C to 70°C	-20°C to 70°C
Storage Temperature	-30°C to 80°C	-30°C to 80°C	-30°C to 80°C
Relative Humidity	-	-	-
Protection	Full IP65	-	-
Certification	CE, e13 (Vehicle), FCC, RoHS	CE, e13 (Vehicle), FCC, RoHS	CE, e13 (Vehicle), FCC, RoHS
Dimensions	205,2 x 139,5 x 28,7 mm (W x H x D)	196 x 121,5 x 35 mm (W x H x D)	196 x 121,5 x 35 mm (W x H x D)
Weight	1,2 Kg	0,7 kg	0,7 kg
Material	Aluminum Casing	-	-
Typ. Application	Industrial, Automotive, Marine, Digital Signage, Outdoor	Industrial, Automotive	Industrial, Automotive

PDF Online Selection Guide
Stand vom 13.05.2024 - 15:57:38

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.

Selection Guide Tough- & Standard Fahrzeugmonitore



7" DeltaToughMon Type 4



7" DeltaToughMon Type 5



7" DeltaToughMon Type 6

Bestellinformation	Artikel-Nr. DMTX3003 7" DeltaToughMon Type 4, 1.024x600 w/ PCT & Full IP65, LCD Monitor, 1.000cd/m², VGA, DVI, HDMI, AV	Artikel-Nr. DMTX3004 7" DeltaToughMon Type 5, 1.024x600 w/o TouchScreen, LCD Monitor, 600cd/m², VGA, DVI, HDMI, AV	Artikel-Nr. DMTX3005 7" DeltaToughMon Type 6, 1.024x600 w/ TouchScreen, LCD Monitor, 600cd/m², VGA, DVI,HDMI, AV
--------------------	--	---	---

PDF Online Selection Guide
Stand vom 13.05.2024 - 15:57:38

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.



7" DeltaToughMon Type 7



7" DeltaToughMon Type 8



8" DeltaToughMon Type 1

LCD Size	7"	7"	8"
Active Area			
Aspect Ratio	16:9	16:9	4:3
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	SVGA (800x600)	WVGA (800x480)	SVGA (800x600)
Display Colors			
Brightness	500 cd/m²	500cd/m²	400cd/m²
Contrast Ratio	400:1	400:1	500:1
Response Time	10 / 15 ms (Tr / Tf)	10 / 15 ms (Tr / Tf)	10 / 15 ms (Tr / Tf)
Viewing Angle	140° / 120° (H / V)	140° / 120° (H / V)	140° / 120° (H / V)
Anti Reflection Glass		x	x
Sunlight Readable			
Gapless Optical Bonding			
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen		Projected Capacitive Multi-Touch	
Cooling System			
Mounting System	360° Copper Monitor Stand Stand	360° Copper Monitor Stand Stand	75mm x 75mm VESA, 360° Copper Monitor Stand or U-Shape Mount Stand
Graphic Interface	VGA/CRT, S-Video	VGA/CRT, S-Video	VGA/CRT
Interface COM			
Interface USB	-	USB	-
Camera			
Video Input			
Reverse camera input			
Audio	3x Audio In	3x Audio In	3x Audio In
Speakers	built-In Speakers	built-In Speakers	built-In Speakers
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	9 to 30VDC	9 to 30VDC	9 to 36VDC
Input Current	< 5W	< 5W	< 14W
Operating Temperature	-20°C to 70°C	-20°C to 70°C	-20°C to 70°C
Storage Temperature	-30°C to 80°C	-30°C to 80°C	-30°C to 80°C
Relative Humidity			
Protection			
Certification	CE, e13 (Vehicle), FCC, RoHs	CE, e1 (Vehicle), MIL-STD-810F, MIL-STD-810G, FCC	CE, e13 (Vehicle), FCC, RoHs
Dimensions	193,97 x 123,97 x 30,5 mm (W x H x D)	193,97 x 123,97 x 30,5 mm (W x H x D)	228x 164x 36 mm (W x H x D)
Weight	0,5 kg	0,5 kg	1,2 Kg
Material			Ruggedized Aluminum Casing
Typ. Application	Industrial, Automotive	Industrial, Automotive	Industrial, Automotive

Selection Guide Tough- & Standard Fahrzeugmonitore



7" DeltaToughMon Type 7



7" DeltaToughMon Type 8



8" DeltaToughMon Type 1

Bestellinformation

Artikel-Nr. DMTX3006

7" DeltaToughMon Type 7, 800x480 w/o
TouchScreen, LCD Monitor, 500cd/m², VGA, AV,
AG-Coating

Artikel-Nr. DMTX3007

7" DeltaToughMon Type 8, 800x480 w/
TouchScreen, LCD Monitor, 500cd/m², VGA, AV,
AG-Coating

Artikel-Nr. DMTX3020

8" DeltaToughMon Type 1, 800x600 w/o
TouchScreen, LCD Monitor, 400cd/m², VGA, AV,
AG-Coating

PDF Online Selection Guide
Stand vom 13.05.2024 - 15:57:38

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.



8" DeltaToughMon Type 2



8" DeltaToughMon Type 3



8" DeltaToughMon Type 4

LCD Size	8"	8"	8"
Active Area			
Aspect Ratio	4:3	4:3	4:3
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	SVGA (800x600)	SVGA (800x600)	SVGA (800x600)
Display Colors			
Brightness	400cd/m²	1.000cd/m²	1.000cd/m²
Contrast Ratio	500:1	500:1	500:1
Response Time	10 / 15 ms (Tr / Tf)	10 / 15 ms (Tr / Tf)	10 / 15 ms (Tr / Tf)
Viewing Angle	140° / 120° (H / V)	140° / 120° (H / V)	140° / 120° (H / V)
Anti Reflection Glass	x	x	x
Sunlight Readable			
Gapless Optical Bonding			
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	5-Wire Resistive Touch	5-Wire Resistive Touch	Touch Interface
Cooling System			
Mounting System	75mm x 75mm VESA, 360° Copper Monitor Stand Stand	75mm x 75mm VESA, 360° Copper Monitor Stand Stand	75mm x 75mm VESA, 360° Copper Monitor Stand Stand
Graphic Interface	VGA/CRT	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI, HDMI	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI, HDMI
Interface COM			
Interface USB	USB	USB	USB
Camera			
Video Input			
Reverse camera input			
Audio	3x Audio In	3x Audio In	3x Audio In
Speakers	built-In Speakers	built-In Speakers	built-In Speakers
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	9 to 36VDC	9 to 36VDC	9 to 36VDC
Input Current	< 14W	< 14W	< 14W
Operating Temperature	-20°C to 70°C	-20°C to 70°C	-20°C to 70°C
Storage Temperature	-30°C to 80°C	-30°C to 80°C	-30°C to 80°C
Relative Humidity			
Protection			
Certification	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs
Dimensions	228x 164x 36 mm (W x H x D)	228x 164x 36 mm (W x H x D)	228x 164x 36 mm (W x H x D)
Weight	1,2 Kg	1,2 Kg	1,2 Kg
Material	Ruggedized Aluminum Casing	Ruggedized Aluminum Casing	Ruggedized Aluminum Casing
Typ. Application	Industrial, Automotive	Industrial, Automotive	Industrial, Automotive

Selection Guide Tough- & Standard Fahrzeugmonitore



8" DeltaToughMon Type 2



8" DeltaToughMon Type 3



8" DeltaToughMon Type 4

Bestellinformation

Artikel-Nr. DMTX3021

8" DeltaToughMon Type 2, 800x600 w/
TouchScreen, LCD Monitor, 400cd/m², VGA, AV,
AG-Coating

Artikel-Nr. DMTX3022

8" DeltaToughMon Type 3, 800x600 w/ GFG-TS
,SR, LCD Monitor, 1.000cd/m², VGA, DVI, HDMI,
AV

Artikel-Nr. DMTX3023

8" DeltaToughMon Type 4, 800x600 w/o
T.Screen,SR, LCD Monitor, 1.000cd/m², VGA, DVI,
HDMI, AV

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.


Selection Guide Tough- & Standard Fahrzeugmonitore



8" DeltaToughMon Type 5



8" DeltaToughMon Type 6



8" DeltaToughMon Type 7

LCD Size	8"	8"	8"
Active Area			
Aspect Ratio	4:3	4:3	4:3
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	SVGA (800x600)	SVGA (800x600)	720p (1.280x720)
Display Colors			
Brightness	400cd/m²	400cd/m²	1.000cd/m²
Contrast Ratio	500:1	500:1	1.000:1
Response Time	10 / 15 ms (Tr / Tf)	10 / 15 ms (Tr / Tf)	15 / 10 ms (Tr / Tf)
Viewing Angle	140° / 120° (H / V)	140° / 120° (H / V)	170° / 170° (H / V)
Anti Reflection Glass	x	x	x
Sunlight Readable			x
Gapless Optical Bonding			x
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	5-Wire Resistive TouchScreen	TouchScreen Interface	5-Wire Resistive Touchscreen
Cooling System			
Mounting System	75mm x 75mm VESA, 360° Copper Monitor Stand	75mm x 75mm VESA, 360° Copper Monitor Stand	Panel Mountable with included hardware Wall Mount, 75mm x 75mm VESA
Graphic Interface	VGA/CRT	VGA/CRT	DVI Input through included DVI to HDMI Adaptor DVI, 2x HDMI
Interface COM			
Interface USB	USB	USB	USB, USB 3.0
Camera			
Video Input			x
Reverse camera input			
Audio	3x Audio In	3x Audio In	3x Audio In
Speakers	built-In Speakers	built-In Speakers	built-In Speakers
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	9 to 36VDC	9 to 36VDC	9 to 36VDC
Input Current	< 14W	< 14W	< 20W
Operating Temperature	-20°C to 70°C	-20°C to 70°C	-35°C to 85°C
Storage Temperature	-30°C to 80°C	-30°C to 80°C	-40°C to 90°C
Relative Humidity			
Protection			
Certification	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs
Dimensions	200 x 163 x 36,5 mm (W x H x D)	200 x 163 x 36,5 mm (W x H x D)	220,7 x 142,7 x 33 mm (W x H x D)
Weight	0,8 Kg	0,85 Kg	0,86 Kg
Material			
Typ. Application	Industrial, Automotive	Industrial, Automotive	Industrial, Automotive


Selection Guide Tough- & Standard Fahrzeugmonitore



8" DeltaToughMon Type 5



8" DeltaToughMon Type 6



8" DeltaToughMon Type 7

Bestellinformation

Artikel-Nr. DMTX3024

8" DeltaToughMon Type 5, 800x600 w/
TouchScreen, LCD Monitor, 400cd/m², VGA, AV,
AG-Coating

Artikel-Nr. DMTX3025

8" DeltaToughMon Type 6, 800x600 w/o
TouchScreen, LCD Monitor, 400cd/m², VGA, AV,
AG-Coating


Artikel-Nr. DMTX3026

8" DeltaToughMon Type 7, 1.280x720 w/ PCT,
IP65, SR, LCD Monitor, 1.000cd/m², HDMI, USB-C,
DVI, Opt.Bond

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.

Selection Guide Tough- & Standard Fahrzeugmonitore



8" DeltaToughMon Type 8




10,1" DeltaToughMon Type 1



10,1" DeltaToughMon Type 2

LCD Size	8"	10,1"	10,1"
Active Area	-	-	-
Aspect Ratio	4:3	16:9	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	720p (1.280x720)	WXGA (1.280x800)	WSVGA (1.024x600)
Display Colors	-	-	-
Brightness	1.000cd/m²	400 cd/m²	400 cd/m²
Contrast Ratio	1.000:1	600:1	600:1
Response Time	15 / 10 ms (Tr / Tf)	5ms / 20 ms (Tr / Tf)	5ms / 20 ms (Tr / Tf)
Viewing Angle	170° / 170° (H / V)	140° / 120° (H / V)	140° / 120° (H / V)
Anti Reflection Glass	x	x	x
Sunlight Readable	x	-	-
Gapless Optical Bonding	x	-	-
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	5-Wire Resistive Touchscreen	-	-
Cooling System	-	-	-
Mounting System	Panel Mountable with included hardware Wall Mount, 75mm x 75mm VESA	75 x 75 mm VESA, Stand	75 x 75 mm VESA, 360° Copper Monitor Stand or U-Shape Mount Stand
Graphic Interface	DVI Input through included DVI to HDMI Adaptor DVI, 2x HDMI	VGA/CRT, DVI, HDMI	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI, HDMI
Interface COM	-	-	-
Interface USB	USB, USB 3.0	-	USB
Camera	-	-	-
Video Input	x	-	-
Reverse camera input	-	-	-
Audio	3x Audio In	3x Audio In	3x Audio In
Speakers	built-In Speakers	built-In Speakers	built-In Speakers
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	9 to 36VDC	9 to 36VDC	9 to 36VDC
Input Current	< 20W	20W	< 20W
Operating Temperature	-35°C to 85°C	-20°C to 70°C	-20°C to 70°C
Storage Temperature	-40°C to 90°C	-30°C to 80°C	-30°C to 80°C
Relative Humidity	-	-	-
Protection	-	-	-
Certification	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs
Dimensions	220,7 x 142,7 x 33 mm (W x H x D)	265 x 186 x 33,2 mm (W x H x D)	265 x 186 x 33,2 mm (W x H x D)
Weight	0,86 Kg	1,45 Kg	1,5 Kg
Material	-	Ruggedized Aluminum casing	Ruggedized Aluminum casing
Typ. Application	Industrial, Automotive	Industrial, Automotive, Digital Signage, Outdoor	Industrial, Automotive, Digital Signage, Outdoor

Selection Guide Tough- & Standard Fahrzeugmonitore



8" DeltaToughMon Type 8



10,1" DeltaToughMon Type 1



10,1" DeltaToughMon Type 2

Bestellinformation

Artikel-Nr. DMTX3027
8" DeltaToughMon Type 8, 1.280x720 w/ PCT,
IP65,SR, LCD Monitor, 1.000cd/m², HDMI, DVI,
AR/AF-Coating

Artikel-Nr. DMTX3060
10,1" DeltaToughMon Type 1 WXGA w/o
TouchScreen, LCD Monitor Alu-Housing,
400cd/m², HDMI/DVI, VGA, AV

Artikel-Nr. DMTX3061
10,1" DeltaToughMon Type 2, 1.024x600, w/
TouchScr, LCD Monitor Alu-Gehäuse,
400cd/m²,HDMI/DVI,VGA,AV

Bitte laden Sie sich bei Bedarf [hier](#) eine aktualisierte Fassung dieses Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.

Selection Guide Tough- & Standard Fahrzeugmonitore



10,1" DeltaToughMon Type 3



10,1" DeltaToughMon Type 4



10,1" DeltaToughMon Type 5

LCD Size	10,1"	10,1"	10,1"
Active Area	-	-	-
Aspect Ratio	16:9	16:9	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WXGA (1.280x800)	WXGA (1.280x800)	WXGA (1.280x800)
Display Colors	-	-	-
Brightness	1.200 cd/m²	1.200 cd/m²	1.200 cd/m²
Contrast Ratio	800:1	800:1	800:1
Response Time	10ms / 15 ms (Tr / Tf)	10ms / 15 ms (Tr / Tf)	10ms / 15 ms (Tr / Tf)
Viewing Angle	170° / 170° (H / V)	170° / 170° (H / V)	170° / 170° (H / V)
Anti Reflection Glass	x	x	x
Sunlight Readable	x	x	x
Gapless Optical Bonding	-	-	-
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	5-Wire Resistive Touchscreen	-	-
Cooling System	-	-	-
Mounting System	75 x 75 mm VESA, 360° Copper Monitor Stand or U-Shape Mount Stand	75 x 75 mm VESA, 360° Copper Monitor Stand or U-Shape Mount Stand	Panel Mountable with Optional Panel Mount Bracket Wall Mount, 75 x 75 mm VESA, 360° Copper Monitor Stand or U-Shape Mount Stand
Graphic Interface	VGA/CRT, DVI Video Signal Input through included DVI to HDMI Adaptor DVI, HDMI	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, HDMI	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, HDMI
Interface COM			
Interface USB	USB	USB	USB
Camera			
Video Input			2x Video Input
Reverse camera input			
Audio	3x Audio In	3x Audio In	3x Audio In
Speakers	built-In Speakers	built-In Speakers	built-In Speakers
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	9 to 36VDC	9 to 36VDC	9 to 36VDC
Input Current	< 20W	< 20W	< 20W
Operating Temperature	-20°C to 70°C	-20°C to 70°C	-20°C to 70°C
Storage Temperature	-30°C to 80°C	-30°C to 80°C	-30°C to 80°C
Relative Humidity	-	-	-
Protection	IEC 60068-2-64, IEC 60068-2-27	IEC 60068-2-64, IEC 60068-2-27	IK07 Impact Resistant, IP65 / NEMA4 Rated Water and Dust Resistance
Certification	CE, e13 (Vehicle), FCC, RoHS	CE, e13 (Vehicle), FCC, RoHS	CE, e13 (Vehicle), FCC, RoHS
Dimensions	265 x 186 x 33,2 mm (W x H x D)	265 x 186 x 33,2 mm (W x H x D)	265 x 186 x 33,2 mm (W x H x D)
Weight	1,5 Kg	1,5 Kg	1,5 Kg
Material	Ruggedized Aluminum casing	Ruggedized Aluminum casing	Ruggedized Aluminum casing
Typ. Application	Industrial, Automotive, Digital Signage, Outdoor	Industrial, Automotive, Digital Signage, Outdoor	Industrial, Automotive, Digital Signage, Outdoor

Selection Guide Tough- & Standard Fahrzeugmonitore



10,1" DeltaToughMon Type 3



10,1" DeltaToughMon Type 4



10,1" DeltaToughMon Type 5

Bestellinformation

Artikel-Nr. DMTX3062
10,1" DeltaToughMon Type 3, 1.280x800,
w/TouScr,SR, LCD Monitor
Alu-Gehäuse,1.200cd/m²,HDMI/DVI,VGA,AV

Artikel-Nr. DMTX3063
10,1" DeltaToughMon Type 4, 1.280x800, w/o
TouScr,SR, LCD Monitor Alu-Gehäuse,
1.200cd/m², HDMI/DVI, VGA, AV

Artikel-Nr. DMTX3064
10,1" DeltaToughMon Type 5, 1.280x800 w/ PCT,
IP65,SR, LCD Monitor AluHou. 1.200cd/m²,
HDMI/DVI, VGA, AV, IK08

PDF Online Selection Guide
Stand vom 13.05.2024 - 15:57:38

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.



10,1" DeltaToughMon Type 6



10,4" DeltaToughMon Type 1



12,1" DeltaToughMon Type 2

LCD Size	10,1"	10,4"	12,1"
Active Area	-	-	-
Aspect Ratio	16:9	4:3	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WXGA (1.280x800)	SVGA (800x600)	WXGA (1.280x800)
Display Colors	-	-	-
Brightness	1.200 cd/m²	300 cd/m²	1.000 cd/m²
Contrast Ratio	800:1	500:1	1.000:1
Response Time	10ms / 15 ms (Tr / Tf)	30 ms / 30 ms (Tr / Tf)	25ms / 25 ms (Tr / Tf)
Viewing Angle	170° / 170° (H / V)	150° / 110° (H / V)	178° / 178° (H / V)
Anti Reflection Glass	x	x	x
Sunlight Readable	x		x
Gapless Optical Bonding	x		x
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	Projected Capacitive Multi-Touch Touchscreen	5-Wire Resistive Touchscreen	Projected Capacitive Multi-Touch Touchscreen
Cooling System	-	-	-
Mounting System	Panel Mountable with Optional Panel Mount Bracket Wall Mount, 75 x 75 mm VESA, 360° Copper Monitor Stand or U-Shape Mount Stand	75 x 75 mm VESA, Removable Stand Stand	Panel Mountable with included hardware Panel Mount Bracket Wall Mount, 75 x 75 mm VESA
Graphic Interface	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, HDMI	1x VGA/CRT, 1x HDMI	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, 2x Input /1x Output HDMI
Interface COM			
Interface USB	USB	-	USB
Camera			
Video Input	2x Video Input		2x Video Input
Reverse camera input			
Audio	3x Audio In		4x Audio In
Speakers	built-In waterproof Speakers		4x built-In waterproof Speakers
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	9 to 36VDC		9 to 36VDC
Input Current	< 20W	< 9W	< 30W
Operating Temperature	-20°C to 70°C	-0°C to 40°C	-30°C to 85°C
Storage Temperature	-30°C to 80°C	-10°C to 50°C	-30°C to 85°C
Relative Humidity	-	-	-
Protection	IP67 / NEMA6P Rated Water and Dust, IK08 Impact Resistant	IP54	IP67 / NEMA6P Rated Water and Dust, IK08 Impact Resistant
Certification	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs	CE, e13 (Vehicle), FCC, RoHs
Dimensions	265,7 x 178,2 x 33,2 mm (W x H x D)	248,9 x 192 x 29 mm (W x H x D)	312 x 230 x 44,2 mm (W x H x D)
Weight	1,7 Kg	1,4 Kg	2,9 Kg
Material	Ruggedized Aluminum casing		
Typ. Application	Industrial, Automotive, Digital Signage, Outdoor	Industrial, Automotive, Marine, Military, Digital Signage	Industrial, Automotive, Digital Signage, Outdoor

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.

Selection Guide Tough- & Standard Fahrzeugmonitore



10,1" DeltaToughMon Type 6



10,4" DeltaToughMon Type 1



12,1" DeltaToughMon Type 2

Bestellinformation	Artikel-Nr. DMTX3065 10,1" DeltaToughMon Type 6, 1.280x800 w/ PCT, IP67, Opt., LCD Monitor Alu-Hou., 1.200cd/m², HDMI/DVI, VGA, AV, IK08	Artikel-Nr. DMTX3040 10,4" DeltaToughMon Type 1, 800x600 w/ TouchScr.IP54, LCD Monitor, 300cd/m², HDMI,VGA,AG-Coating	Artikel-Nr. DMTX3071 12,1" DeltaToughMon Type 2, 1.280x800 w/ PCT,IP67,Opt, LCD Monitor AluHous., 1000cd/m², HDMI/DVI, VGA, AV, IK08
--------------------	---	--	---

PDF Online Selection Guide
Stand vom 13.05.2024 - 15:57:38

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.



12,1" DeltaToughMon Type 3



12,1" DeltaToughMon Type 4



12,1" DeltaToughMon Type 1

LCD Size	12,1"	12,1"	12,1"
Active Area	-	-	-
Aspect Ratio	16:9	16:9	4:3
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WXGA (1.280x800)	WXGA (1.280x800)	XGA (1.024x768)
Display Colors	-	-	-
Brightness	1.000 cd/m²	1.000 cd/m²	500 cd/m²
Contrast Ratio	1.000:1	1.000:1	700:1
Response Time	25ms / 25 ms (Tr / Tf)	25ms / 25 ms (Tr / Tf)	26 ms / 26 ms (Tr / Tf)
Viewing Angle	178° / 178° (H / V)	178° / 178° (H / V)	160° / 140° (H / V)
Anti Reflection Glass	x	x	x
Sunlight Readable	x	x	
Gapless Optical Bonding	x	x	
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	Projected Capacitive Multi-Touch Touchscreen	Projected Capacitive Multi-Touch Touchscreen	5-Wire Resistive Touchscreen
Cooling System	-	-	-
Mounting System	Panel Mountable with included hardware Panel Mount Bracket Wall Mount, 75 x 75 mm VESA	Panel Mountable with included hardware Panel Mount Bracket Wall Mount, 75 x 75 mm VESA	75 x 75 mm VESA, Monitor Stand incl. Stand
Graphic Interface	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, 2x Input /1x Output HDMI, 1x SDI Input, 1x SDI Output SDI	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, 2x Input /1x Output HDMI, 1x SDI Input, 1x SDI Output SDI	VGA/CRT, 1x DVI Input DVI to HDMI Adaptor DVI
Interface COM			
Interface USB	USB	USB, 1x USB-C 3.1 USB 3.0	-
Camera			
Video Input	2x Video Input	2x Video Input	
Reverse camera input			
Audio	4x Audio In	4x Audio In	
Speakers	4x built-In waterproof Speakers	4x built-In waterproof Speakers	
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	9 to 36VDC	9 to 36VDC	
Input Current	< 30W	< 30W	< 20W
Operating Temperature	-30°C to 85°C	-30°C to 85°C	-0°C to 40°C
Storage Temperature	-30°C to 85°C	-30°C to 85°C	-10°C to 50°C
Relative Humidity	-	-	-
Protection	IP67 / NEMA6P Rated Water and Dust, IK08 Impact Resistant	IP67 / NEMA6P Rated Water and Dust, IK08 Impact Resistant	IP54
Certification	CE, e13 (Vehicle), FCC, RoHS	CE, e13 (Vehicle), FCC, RoHS	CE, e13 (Vehicle), FCC, RoHS
Dimensions	312 x 230 x 44,2 mm (W x H x D)	312 x 230 x 44,2 mm (W x H x D)	315 x 255 x 67,7 mm (W x H x D)
Weight	2,9 Kg	2,9 Kg	3,5 Kg
Material			
Typ. Application	Industrial, Automotive, Digital Signage, Outdoor	Industrial, Automotive, Digital Signage, Outdoor	Industrial, Automotive, Marine, Military, Digital Signage

Selection Guide Tough- & Standard Fahrzeugmonitore



12,1" DeltaToughMon Type 3



12,1" DeltaToughMon Type 4



12,1" DeltaToughMon Type 1

Bestellinformation

Artikel-Nr. DMTX3072

12,1" DeltaToughMon Type 3, 1280x800 w/
PCT, IP67, Opt., LCD Mon. Alu-Hou.,
1000cd/m², HDMI/SDI/DVI, VGA, AV, IK08

Artikel-Nr. DMTX3073

12,1" DeltaToughMon Type 4, 1280x800 w/
PCT, IP67, Opt.B, LCD Moni. Alu-Hou.,
1000cd/m², HDMI/USB-C/AV/VGA/IK08

Artikel-Nr. DMTX3070

12,1" DeltaToughMon Type 1, 1.024x600 w/
TouchS, IP54, LCD Monitor, 500cd/m²,
DVI, VGA, AG-Coating

PDF Online Selection Guide
Stand vom 13.05.2024 - 15:57:38

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.



15,6" DeltaToughMon Type 1



15" DeltaToughMon Type 1



24" DeltaToughMon Type 1

LCD Size	15,6"	15"	24"
Active Area	-	-	-
Aspect Ratio	16:9	4:3	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WXGA (1.280x800)	XGA (1.024x768)	WXGA (1.280x800), 1080p (1.920x1.080)
Display Colors	-	-	-
Brightness	1.000 cd/m²	300 cd/m²	1.000 cd/m²
Contrast Ratio	800:1	500:1	5.000:1
Response Time	13ms / 12 ms (Tr / Tf)	30 ms / 30 ms (Tr / Tf)	25ms / 25 ms (Tr / Tf)
Viewing Angle	170° / 170° (H / V)	160° / 160° (H / V)	178° / 178° (H / V)
Anti Reflection Glass	x	x	x
Sunlight Readable	x	-	x
Gapless Optical Bonding	x	-	-
MTBF	55.000 hours	55.000 hours	55.000 hours
TouchScreen	Projected Capacitive Multi-Touch Touchscreen	Projected Capacitive Multi-Touch Touchscreen	Sunlight Readable and Capacitive Touchscreen
Cooling System	-	-	-
Mounting System	Panel Mountable with included hardware Panel Mount Bracket Wall Mount, 75 x 75 mm VESA	75 x 75 mm VESA, Removable Stand Stand	Panel Mount Bracket Wall Mount, 100mm x 100 mm, 200mm x 100mm VESA
Graphic Interface	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, 2x Input/1x Output HDMI	1x VGA/CRT, 1x HDMI	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, 1x Input HDMI
Interface COM	-	-	-
Interface USB	USB	USB	USB
Camera	-	-	-
Video Input	2x Video Input, 1x Analog Audio Output	-	-
Reverse camera input	-	-	-
Audio	4x Audio In	-	4x Audio In
Speakers	4x built-In waterproof Speakers	-	4x built-In waterproof Speakers
Input Voltage Nominal	12VDC	12VDC	12VDC
Input Voltage Min/Max	9 to 36VDC	-	12VDC
Input Current	< 30W	< 18W	< 45W
Operating Temperature	-30°C to 85°C	-0°C to 40°C	-30°C to 70°C
Storage Temperature	-40°C to 90°C	-15°C to 50°C	-30°C to 75°C
Relative Humidity	-	-	-
Protection	IP67 / NEMA6P Rated Water and Dust, IK08 Impact Resistant	IP54	IP69K, IP66 / NEMA4X Impact Resistant
Certification	CE, e13 (Vehicle), FCC, RoHS	CE, e13 (Vehicle), FCC, RoHS	CE, e13 (Vehicle), FCC, RoHS
Dimensions	398 x 264 x 44,7 mm (W x H x D)	360,6 x 290,5 x 34,9 mm (W x H x D)	608 x 392 x 54 mm (W x H x D)
Weight	4,1 Kg	3,3 kg	10,3 Kg
Material	Ruggedized Aluminum Casing	-	Ruggedized Stainless-Steel Casing
Typ. Application	Industrial, Automotive, Digital Signage, Outdoor	Industrial, Automotive, Marine, Military, Digital Signage	Industrial, Automotive, Marine, Military, Digital Signage, Outdoor

Selection Guide Tough- & Standard Fahrzeugmonitore



15,6" DeltaToughMon Type 1



15" DeltaToughMon Type 1



24" DeltaToughMon Type 1

Bestellinformation

Artikel-Nr. DMTX3080

15,6" DeltaToughMon Typ1, 1.280x800 w/ PCT,
IP67, Opt, LCD Monitor AluHou.,
1.000cd/m², HDMI/DVI, VGA, AV, IK08

Artikel-Nr. DMTX3050

15" DeltaToughMon Type 1, 1.024x768 w/ PCT,
IP54, LCD Monitor, 300cd/m²,
HDMI, VGA, AG-Coating

Artikel-Nr. DMTX3090

24" DeltaToughMon Typ1, 1920x1.080 w/ PCT,
IP69K, IP66, LCD Mon. stainl.SteelHo.1000cd/m²,
HDMI/DVI, VGA, USB

Bitte laden Sie sich bei Bedarf [hier](#) eine aktualisierte Fassung dieses Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.

Selection Guide Tough- & Standard Fahrzeugmonitore



24" DeltaToughMon Type 2



Vehicle Mount Display 1001



Vehicle Mount Display 2003

LCD Size	24"	7.0"	8.0"
Active Area	-	-	-
Aspect Ratio	16:9	-	-
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WXGA (1.280x800), 1080p (1.920x1.080)	WVGA (800x480)	SVGA (800x600)
Display Colors	-	-	-
Brightness	1.000 cd/m²	500 cd/m²	800 cd/m²
Contrast Ratio	5.000:1	600:1	500:1
Response Time	25ms / 25 ms (Tr / Tf)	-	-
Viewing Angle	178° / 178° (H / V)	-	-
Anti Reflection Glass	x	x	-
Sunlight Readable	x	Optional	x
Gapless Optical Bonding	-	-	-
MTBF	55.000 hours	-	-
TouchScreen	-	4-wire resistive	4-wire resistive touch
Cooling System	-	-	Fanless
Mounting System	Panel Mount Bracket Wall Mount, 100mm x 100 mm, 200mm x 100mm VESA	VESA, Stand	VESA, Stand
Graphic Interface	VGA/CRT, DVI Input through included DVI to HDMI Adaptor DVI to HDMI Adaptor DVI, 1x Input HDMI	VGA/CRT	1x DB9 (female) for up to 4x analog cameras input Composite/CVBS, UltraONE+
Interface COM	-	-	-
Interface USB	USB	2x USB	1x USB 2.0
Camera	-	-	Optional
Video Input	-	-	1x DB9 (male) for ultraONE+ technology
Reverse camera input	-	-	-
Audio	4x Audio In	1x Line-In, 1x Line-Out	1x Line-out, 1x Mic-in
Speakers	4x built-in waterproof Speakers	-	2x (1.2W)
Input Voltage Nominal	12VDC	-	12VDC
Input Voltage Min/Max	12VDC	6 to 36VDC	-
Input Current	< 45W	-	-
Operating Temperature	-30°C to 70°C	-20°C to 70°C	-20°C to 60°C
Storage Temperature	-30°C to 75°C	-30°C to 80°C	-30°C to 70°C
Relative Humidity	-	-	-
Protection	IP69K, IP66 / NEMA4X Impact Resistant	-	IP54 (front), Vibration & Shock
Certification	CE, e13 (Vehicle), FCC, RoHs	CE	CE, MIL-STD-810F, Class B FCC
Dimensions	608 x 392 x 59 mm (W x H x D)	182 x 138 x 36.3 mm	207 x 173 x 36,7 mm (W x H x D)
Weight	10,9 Kg	0.45kg	0,8 kg
Material	Ruggedized Stainless-Steel Casing	-	Plastic PC + ABS
Typ. Application	Industrial, Automotive, Marine, Military, Digital Signage, Outdoor	Industrial, Automotive	Industrial, Automotive

Selection Guide Tough- & Standard Fahrzeugmonitore



24" DeltaToughMon Type 2



Vehicle Mount Display 1001



Vehicle Mount Display 2003

Bestellinformation

Artikel-Nr. DMTX3091
24" DeltaToughMon Typ2, 1920x1080 w/o
TS, IP69K, IP66, LCD Mon.
stainl. Steel Ho. 1000cd/m², HDMI/DVI, VGA, USB

Artikel-Nr. DMXX1080
VMD 1001, 7" w/ resistive TouchScreen
"VGA-direct", 500cd/m², WVGA, 1x VGA, 1x
Line-In/-Out, 2x USB

Artikel-Nr. DMXX1080-1
VMD 1001, 7" w/ resistive TouchScreen, sunlight
readable "VGA-direct", 500cd/m², WVGA, 1x VGA,
1x Line-In/-Out, 2x USB

Artikel-Nr. DMXX1080-2
VMD 1001, 7" w/ resistive TouchScreen, camera
"VGA-direct", 500cd/m², WVGA, 1x VGA, 1x
Line-In/-Out, 2x USB

Artikel-Nr. DMXX1080-3
VMD 1001, 7" w/ resistive TouchScreen, sunlight
readable, camera "VGA-direct", 500cd/m², WVGA,
1x VGA, 1x Line-In/-Out, 2x USB

Artikel-Nr. DMXX1087
VMD 2003-BS, 8,0" w/ resistive TouchScreen
"ultraONE", 800cd/m², SVGA, 4x CVBS, 1x USB,
ultraONE+ video-in

Artikel-Nr. PKBX5326
VTC 1011-C2VK, w/ Intel Atom E3825, Dual Core
1.33GHz, 1x VGA, 1x HDMI, 3x COM, 1x CAN, 2x
PoE, ultraONE+ video-out

Artikel-Nr. PKBX5900
ATC 8010 w/ Intel® Core i7-8700T 6-core & GTX
1050Ti, 1x VGA, 5x HDMI, 3x COM, 8x PoE, 8GB
DDR4, ultraONE+ video-out

Artikel-Nr. PKBX5901
ATC 8010 w/ Intel® Core i7-8700T 6-core, 1x
VGA, 5x HDMI, 3x COM, 8x PoE, 8GB DDR4,
ultraONE+ video-out

Artikel-Nr. BPLK1137
ultraOne+ All-in-One Cable 10 Meter, D-SUB HD 9
connector, USB, Power, Video & Audio

Artikel-Nr. BPLK1138
ultraOne+ All-in-One Cable 5 Meter, D-SUB HD 9
connector, USB, Power, Video & Audio

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.

Selection Guide Tough- & Standard Fahrzeugmonitore



Vehicle Mount Display 2002



Vehicle Mount Display 2000



Vehicle Mount Display 3002

LCD Size	8.0"	8.0"	10.4"
Active Area	-	-	-
Aspect Ratio			-
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	SVGA (800x600)	SVGA (800x600)	XGA (1.024x768)
Display Colors	-	-	-
Brightness	400 cd/m² (800 cd/m² optional)	400 cd/m² / 800 cd/m² optional	1.200 cd/m²
Contrast Ratio	500:1	500:1	500:1
Response Time	-	-	-
Viewing Angle	-	-	-
Anti Reflection Glass	X	-	-
Sunlight Readable	Optional	Optional	-
Gapless Optical Bonding	-	-	-
MTBF	-	-	-
TouchScreen	4-wire resistive touch	4-wire resistive	Projected capacitive TouchScreen
Cooling System	Fan	-	-
Mounting System	VESA, Stand	Wall Mount, VESA, Stand	VESA
Graphic Interface	VGA/CRT	LCD-LVDS	VGA/CRT, 4x Composite/CVBS
Interface COM			
Interface USB	1x USB 2.0	1x USB	1x USB
Camera	Optional	Optional	-
Video Input	-	-	-
Reverse camera input	-	-	-
Audio	1x Line-in, Mic-out, Line-out, Mic-in	1x Line-in, 1x Line-Out, 1x Mic-in, 1x Mic-out, 2x Speaker (1W)	1x Line-in
Speakers	2x (1.2W)	-	-
Input Voltage Nominal	-	12VDC	-
Input Voltage Min/Max	6 to 36 VDC	-	9 to 36VDC
Input Current	-	-	18W
Operating Temperature	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C
Storage Temperature	-30°C to 70°C	-30°C to 70°C	-30°C to 80°C
Relative Humidity	-	-	-
Protection	IP54 (front)	IP54	-
Certification	CE, FCC	CE, MIL-STD-810F, FCC	CE, FCC
Dimensions	207 x 173 x 36.7 mm	207 x 173 x 36.7 mm	256.5 x 202.1 x 31.5 mm
Weight	0,5 kg	0.7kg	1.64kg
Material	-	Plastic PC + ABS	Plastic PC & ABS
Typ. Application	Industrial, Automotive	Industrial, Automotive	Industrial, Automotive

Selection Guide Tough- & Standard Fahrzeugmonitore



Vehicle Mount Display 2002



Vehicle Mount Display 2000



Vehicle Mount Display 3002

Bestellinformation

Artikel-Nr. DMXX1086
VMD 2002, 8" w/ resistive Touch "VGA-one cable",
400cd/m², SVGA, 1x VGA, 1x Line-In/-Out, 1x USB

Artikel-Nr. DMXX1086-1
VMD 2002, 8" w/ resistive Touch, sunlight readable
"VGA-one cable", 800cd/m², SVGA, 1x VGA, 1x
Line-In/-Out, 1x USB

Artikel-Nr. DMXX1086-2
VMD 2002, 8" w/ resistive Touch, camera
"VGA-one cable", 400cd/m², SVGA, 1x VGA, 1x
Line-In/-Out, 1x USB

Artikel-Nr. DMXX1086-3
VMD 2002, 8" w/ resistive Touch, sunlight
readable, camera "VGA-one cable", 800cd/m²,
SVGA, 1x VGA, 1x Line-In/-Out, 1x USB

Artikel-Nr. PKBD1103
VMD 2000, 8" w/ resistive TouchScreen "LVDS",
400cd/m², SVGA, 1x LVDS, 1x Mic-In/-Out, 1x
USB

Artikel-Nr. PKBD1103-1
VMD 2000, 8" w/ resistive TouchScreen, sunlight
readable "LVDS", 800cd/m², SVGA, 1x LVDS, 1x
Mic-In/-Out, 1x USB

Artikel-Nr. PKBD1103-2
VMD 2000, 8" w/ resistive TouchScreen, camera
"LVDS", 400cd/m², SVGA, 1x LVDS, 1x
Mic-In/-Out, 1x USB

Artikel-Nr. PKBD1103-3
VMD 2000, 8" w/ resistive TouchScreen, sunlight
readable, camera "LVDS", 800cd/m², SVGA, 1x
LVDS, 1x Mic-In/-Out, 1x USB

Artikel-Nr. DMXX1090
VMD 3002-BS, 10,4" w/ projected capacitive
TouchScreen "VGA-direct", 1.200 cd/m², XGA, 1x
VGA + 4x CVBS, IP65

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.

Selection Guide Tough- & Standard Fahrzeugmonitore



Vehicle Mount Display 3110

LCD Size	10,4"
Active Area	-
Aspect Ratio	-
Display Backlight	LED Backlight
Display Resolution	XGA (1.024x768)
Display Colors	-
Brightness	1.200 cd/m²
Contrast Ratio	500:1
Response Time	-
Viewing Angle	-
Anti Reflection Glass	-
Sunlight Readable	-
Gapless Optical Bonding	-
MTBF	-
TouchScreen	Projected capacitive TouchScreen
Cooling System	-
Mounting System	VESA, Stand
Graphic Interface	1x DB9 (female) for up to 4x analog cameras input Composite/CVBS, UltraONE+
Interface COM	1x TX/RX
Interface USB	1x USB
Camera	Optional
Video Input	1x DB9 (male) for ultraONE+ technology
Reverse camera input	-
Audio	1x Line-in
Speakers	2x (1W / 8ohm)
Input Voltage Nominal	-
Input Voltage Min/Max	9 to 36VDC
Input Current	18W
Operating Temperature	-20°C to 60°C
Storage Temperature	-30°C to 80°C
Relative Humidity	-
Protection	IP65, Vibration & Shock
Certification	CE, MIL-STD-810G, Class B FCC
Dimensions	256,5 x 202,1 x 31,5 mm (W x D x H)
Weight	1,64 kg
Material	Plastic PC + ABS; Surface hardness 6H
Typ. Application	Industrial, Automotive

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

37 Artikel aus dem Bereich
Tough- & Standard Fahrzeugmonitore
wurden für das PDF ausgewählt.



Vehicle Mount Display 3110

Bestellinformation

Artikel-Nr. DMXX1091

VMD 3110-4PH, 10,4" w/ Projected capacitive
TouchScreen "ultraONE", 1.200cd/m², XGA,
ultraONE+ with USB, 4x CVBS video-in

Artikel-Nr. PKBX5326

VTC 1011-C2VK, w/ Intel Atom E3825, Dual Core
1.33GHz, 1x VGA, 1x HDMI, 3x COM, 1x CAN, 2x
PoE, ultraONE+ video-out

Artikel-Nr. PKBX5900

ATC 8010 w/ Intel® Core i7-8700T 6-core & GTX
1050Ti, 1x VGA, 5x HDMI, 3x COM, 8x PoE, 8GB
DDR4, ultraONE+ video-out

Artikel-Nr. PKBX5901

ATC 8010 w/ Intel® Core i7-8700T 6-core, 1x
VGA, 5x HDMI, 3x COM, 8x PoE, 8GB DDR4,
ultraONE+ video-out

Artikel-Nr. BPLK1137

ultraOne+ All-in-One Cable 10 Meter, D-SUB HD 9
connector, USB, Power, Video & Audio

Artikel-Nr. BPLK1138

ultraOne+ All-in-One Cable 5 Meter, D-SUB HD 9
connector, USB, Power, Video & Audio

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

<https://www.delta-components.de>

<https://www.automotive-computing.com>