

Selection Guide

Marine IP6x High-Performance Monitore

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

www.delta-components.de

www.automotive-computing.com

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



7" Einbaumonitor Full IP65 Typ 1



7" Einbaumonitor Front IP65 Typ 1



7" Einbaumonitor Front IP65 Typ 2

LCD Size	7"	7"	7"
Active Area	155 x 87,5 mm (H x V)	154,2 x 85,9 mm	154,2 x 85,9 mm
Pixel Pitch	-	-	-
Aspect Ratio	16:9	16:9	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WSVGA (1.024x600)	WSVGA (1.024x600)	WSVGA (1.024x600)
Display Colors	262K	262K	262K
Brightness	1.000 cd/m²	1.000 cd/m²	500 cd/m²
Contrast Ratio	700:1	800:1	700:1
Response Time	10 ms / 15 ms (Tr / Tf)	10 ms / 12 ms (Tr / Tf)	10 ms / 15 ms (Tr / Tf)
Viewing Angle	150° / 145° (H / V)	150° / 145° (H / V)	150° / 145° (H / V)
ScanFrequency	-	-	-
Anti Reflection Glass	x	x	-
Strengthened Glass	3H Surface Hardness	7H Surface Hardness, optically bonded	7H Surface Hardness
Sunlight Readable	-	-	-
Gapless Optical Bonding	-	-	x
MTBF	40.000 hours	100.000 h	20.000 hours
TouchScreen	4-Wire resistive	PCT	Projected Capacitive 10-point Multi-touch
Keypad	2 Key	x	5 Key
OSDMenu	-	-	-
Cooling System	-	Fanless	-
Mounting System	75 x 75 mm VESA	100 x 100 mm VESA	75 x 75 mm VESA
Graphic Interface	HDMI	VGA/CRT, DVI, HDMI	VGA/CRT, HDMI, DisplayPort
Interface COM			
Interface USB	USB-Touch USB	1x USB	USB-Touch USB
Video Input			
Video Output			
Audio	optional	1x PC-Audio	x
Speakers	-		-
Operating System			
Operating System Support	Touch Panel Drivers: Windows, Linux, Mac, Android	Windows, Linux, Mac, Android	Touch Panel Drivers: Windows, Linux, Mac, Android
Input Voltage Nominal	-	-	12VDC
Input Voltage Min/Max	8 to 36VDC	12VDC	-
Input Current	10W	10W	7W
Operating Temperature	-25 °C to 75 °C	-10°C to 60°C	-10 °C to 60 °C
Storage Temperature	-	-	-
Relative Humidity	10% to 90%	10% to 90%	10% to 90%
Protection	Full IP65	IP65 front housing / IP40 back housing	IP65 front / IP40 back
Certification	-	CE, FCC	CE, FCC
Dimensions	214 x 134 x 38,5 mm (L x W x H)	210 x 144,5 x 43 mm (L x W x H)	195,6 x 137,6 x 38,5 mm (L x W x H)
Weight	1,1 Kg	0,5 kg	0,95 kg
Material	Aluminum Housing	Aluminium	Silicone edge, ABS plastic Back housing
Typ. Application	Industrial, Digital Signage, Outdoor	Industrial, Marine, Digital Signage, Outdoor	Industrial, Digital Signage, Outdoor
Bestellinformation	Artikel-Nr. DMXX3702-1 7" Einbaumonitor Full IP65 Typ 1, 8 to 36VDC IN, Resistive T., 1.000cd/m², 1.024x600, HDMI	Artikel-Nr. DMXX3701-1 7" Einbaumonitor Front IP65 Typ 1, Optical Bonding, LED Backlight, PCT, 1.000cd/m², 1.024x600, VGA + DVI-D + HDMI, 12VDC In	Artikel-Nr. DMXX3770-1 7" Einbaumonitor Front IP65 Type 2, Optical Bonding, PCT, 500cd/m², 1.024x600, VGA+DP+HDMI, 12VDC In

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



8" Einbaumonitor Full IP65 Typ 1



8" Einbaumonitor Front IP65 Typ 1



8,4" IP65/68 Marine Monitor Typ 3, IP68

LCD Size	8"	8"	8,4"
Active Area	163,4 x 122,9 mm (H x V)	162 x 122 mm (H x V)	170.4 x 127.8mm
Pixel Pitch	-	-	0.213 x 0.213mm (H/V)
Aspect Ratio	4:3	4:3	
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	XGA (1.024x768)	XGA (1.024x768)	SVGA (800x600)
Display Colors	16,7M	16.7M	16.2M
Brightness	1.000 cd/m²	350 cd/m²	1.000cd/m²
Contrast Ratio	700:1	700:1	450:1
Response Time	6 ms / 14 ms (Tr / Tf)	6 ms / 14 ms (Tr / Tf)	35ms
Viewing Angle	150° / 150° (H / V)	150° / 150° (H / V)	130°/115° (H/V)
ScanFrequency	-	-	-
Anti Reflection Glass	x	-	-
Strengthened Glass	3H Surface Hardness	7H Surface Hardness	-
Sunlight Readable	-	-	x
Gapless Optical Bonding	-	x	x
MTBF	40.000 hours	20.000 hours	-
TouchScreen	4-Wire resistive	Projected Capacitive 10-point Multi-touch	IR Touch Screen
Keypad	2 Key	5 Key	-
OSDMenu	-	-	x
Cooling System	-	-	Fan
Mounting System	75 x 75 mm VESA	75 x 75 mm VESA	VESA
Graphic Interface	HDMI	VGA/CRT, HDMI, DisplayPort	1x VGA/CRT
Interface COM			
Interface USB	USB-Touch USB	USB-Touch USB	1x USB
Video Input			-
Video Output			-
Audio	optional	x	
Speakers	-	-	
Operating System			
Operating System Support	Touch Panel Drivers: Windows, Linux, Mac, Android	Touch Panel Drivers: Windows, Linux, Mac, Android	
Input Voltage Nominal	-	12VDC	-
Input Voltage Min/Max	8 to 36VDC	-	9 to 36VDC
Input Current	12W	6W	9,5W
Operating Temperature	-25 °C to 75 °C	-10 °C to 60 °C	-20°C to 60°C
Storage Temperature	-	-	-30°C to 75°C
Relative Humidity	10% to 90%	10% to 90%	-
Protection	Full IP65	IP65 front / IP40 back	IP65, 68
Certification	-	CE, FCC, RoHs	CE, FCC
Dimensions	232 x 172 x 39,5 mm (L x W x H)	201 x 160,5 x 357 mm (L x W x H)	250 x 200 x 64mm
Weight	1,5 Kg	0,75 kg	3kg
Material	Aluminum Housing	Rubber front case and plastic back case	Rugged Aluminum Alloy Chassis
Typ. Application	Industrial, Digital Signage, Outdoor	Industrial, Digital Signage, Outdoor	Industrial, Marine, Outdoor
Bestellinformation	Artikel-Nr. DMXX3700-1 8" Einbaumonitor Full IP65 Type 1, 8 to 36VDC IN, Resistive T., 1.000cd/m², 1.024x768, HDMI	Artikel-Nr. DMXX3775 8" Einbaumonitor Front IP65 Typ 1, 12VDC ,Opt.Bond, PCT, 350cd/m², 1.024x768, VGA+DP+HDMI	Artikel-Nr. DMWX1000-1 8.4" Marine Monitor Typ 3 w/USB TouchScreen, IP68, LED backlight, 1.000 nits, SVGA resol., VGA Artikel-Nr. DMWX1001-1 8.4" Marine Monitor Typ 3 w/anti-reflection glass, IP68, LED backlight, 1.000 nits, SVGA resol., VGA

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



8,4" IP65/68 Marine Monitor Typ 1 - RS232, IP68



9,7" Einbaumonitor Full IP65 Typ 1



10" Einbaumonitor Front IP65 Typ 1

LCD Size	8,4"	9,7"	10"
Active Area	170,4 x 127,8 mm (H/V)	202,8 x 152 mm (H x V)	197 x 147 mm (H x V)
Pixel Pitch	0.213 x 0.213 mm (H/V)	-	-
Aspect Ratio		4:3	4:3
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	SVGA (800x600)	XGA (1.024x768)	XGA (1.024x768)
Display Colors	16.2M	16,7M	16.7M
Brightness	1.000 cd/m²	350 cd/m²	250 cd/m²
Contrast Ratio	600:1	800:1	800:1
Response Time	30ms	10 ms / 15 ms (Tr / Tf)	10 ms / 15 ms (Tr / Tf)
Viewing Angle	120°/120° (H/V)	170° / 170° (H / V)	170° / 170° (H / V)
ScanFrequency	-	-	-
Anti Reflection Glass	x	x	-
Strengthened Glass	-	3H Surface Hardness	7H Surface Hardness
Sunlight Readable	x	-	x
Gapless Optical Bonding	x	-	x
MTBF	-	20.000 hours	20.000 hours
TouchScreen	RS232 IR-TouchScreen	5-Wire resistive	Projected Capacitive 10-point Multi-touch
Keypad	-	2 Key	5 Key
OSDMenu	x	-	-
Cooling System	Fan	-	-
Mounting System	VESA	75 x 75 mm VESA	100 x 100 mm VESA
Graphic Interface	1x VGA/CRT	HDMI	VGA/CRT, HDMI, DisplayPort
Interface COM	1x RS232		
Interface USB	-	USB-Touch USB	USB-Touch USB
Video Input	-		
Video Output	-		
Audio	-	optional	x
Speakers	-	-	-
Operating System			
Operating System Support		Touch Panel Drivers: Windows, Linux, Mac, Android	Touch Panel Drivers: Windows, Linux, Mac, Android
Input Voltage Nominal	12VDC	-	12VDC
Input Voltage Min/Max	9 to 36VDC	8 to 36VDC	-
Input Current	24W	8W	8W
Operating Temperature	-20°C to 60°C	-25 °C to 75 °C	-10 °C to 60 °C
Storage Temperature	-30°C to 80°C	-	-
Relative Humidity	-	10% to 90%	10% to 90%
Protection	IP65, 68	Full IP65	IP65 front / IP40 back
Certification	-	-	CE, FCC, RoHs
Dimensions	250 x 200 x 64 mm	257,2 x 196,4 x 39,5 mm (L x W x H)	244,9 x 195,8 x 39 mm (L x W x H)
Weight	3kg	1,8 Kg	0,9 kg
Material	Rugged Aluminum Alloy Chassis	Aluminum Housing	Silicone edge, ABS plastic Back housing
Typ. Application	Industrial, Marine, Outdoor	Industrial, Digital Signage, Outdoor	Industrial, Digital Signage, Outdoor
Bestellinformation	Artikel-Nr. DMWX1002 8.4" Marine Monitor Typ1 w/RS232 IR-TouchScreen, IP68, LED backlight, 1.000 nits, SVGA resolution, VGA	Artikel-Nr. DMXX3703-1 9,7" Einbaumonitor Full IP65 Type 1, 8 to 36VDC IN, Resistive T., 350cd/m², 1.024x768, HDMI	Artikel-Nr. DMXX3777-1 10" Einbaumonitor Front IP65 Typ1,Optical Bonding, PCT, 250cd/m², 1.024x768, VGA+DP+HDMI, 12VDC In

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



10,1" Einbaumonitor Front IP65 Typ 2



11,6" Einbaumonitor Front IP65 Typ 1

12,1" DeltaToughMon Rahmenloser
Monitor IEC-60945

LCD Size	10,1"	11,6"	12,1"
Active Area	217 x 136 mm (H x V)	256,3 x 144,2 mm	-
Pixel Pitch	-	-	-
Aspect Ratio	16:10	16:9	-
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WXGA (1.280x800)	1080p (1.920x1.080)	XGA (1.024x768)
Display Colors	16.7M	16,7 M	-
Brightness	350 cd/m²	1.000 cd/m²	500 cd/m², Optional backlight 1.000–1.500 cd/m²
Contrast Ratio	800:1	800:1	700:1
Response Time	10ms / 15 ms (Tr / Tf)	14 ms / 11 ms (Tr / Tf)	-
Viewing Angle	170° / 170° (H / V)	178° / 178° (H / V)	160° / 160° (H / V)
ScanFrequency	-	-	-
Anti Reflection Glass	x	x	-
Strengthened Glass	7H Surface Hardness	7H Surface Hardness, optically bonded	-
Sunlight Readable	-	-	optional
Gapless Optical Bonding	x	-	-
MTBF	20.000 hours	100.000 h	-
TouchScreen	Projected Capacitive 10-point Multi-touch	PCT	Projected Capacitive Multi-Touch Touchscreen
Keypad	5 Key	x	x
OSDMenu	-	-	-
Cooling System	-	Fanless	-
Mounting System	100 x 100 mm VESA	100 x 100 mm VESA	Panel Mount, VESA Mount Wall Mount, 75x75mm/100x100mm VESA
Graphic Interface	VGA/CRT, HDMI, DisplayPort	VGA/CRT, DVI, HDMI	1x(15 pin HD-SUB) VGA/CRT, DVI, HDMI
Interface COM	-	-	-
Interface USB	USB-Touch USB	1x USB	USB
Video Input	-	-	-
Video Output	-	-	-
Audio	x	1x PC-Audio	-
Speakers	-	-	-
Operating System	-	-	-
Operating System Support	Touch Panel Drivers: Windows, Linux, Mac, Android	Windows, Linux, Mac, Android	-
Input Voltage Nominal	12VDC	-	12VDC (Optional DC 9–36V)
Input Voltage Min/Max	-	12VDC	-
Input Current	10W	12W	-
Operating Temperature	-10 °C to 60 °C	-10°C to 60°C	-40 – 80 °C or -20 – 60 °C
Storage Temperature	-	-	-40 – 80 °C or -20 – 60 °C
Relative Humidity	10% to 90%	10% to 90%	-
Protection	IP65 front / IP40 back	IP65 front housing / IP40 back housing	IP65 / IP66
Certification	CE, FCC, RoHs	CE, FCC	CE, e13 (Vehicle), FCC, IEC 60945
Dimensions	278 x 203,6 x 33,3 mm (L x W x H)	297,1 x 194 x 40,3 mm (L x W x H)	294 x 224,5 x 50 mm (W x H x D)
Weight	0,9 Kg	2 kg	-
Material	Silicone edge, ABS plastic Back housing	Steel (zinc-coated)	Ruggedized Aluminium Casing
Typ. Application	Industrial, Digital Signage, Outdoor	Industrial, Marine, Digital Signage, Outdoor	Industrial, Automotive, Marine, Digital Signage, Outdoor
Bestellinformation	Artikel-Nr. DMXX3705-3 10,1" Einbaumonitor Front IP65 Typ 2, Opt.Bonding, PCT, 350cd/m², 1.280x800,VGA+DP+HDMI, 12VDC In	Artikel-Nr. DMXX3704 11,6" Einbaumonitor Front IP65 Typ 1, Optical Bonding, LED Backlight, PCT, 1.000cd/m², 1.920x1.080, VGA + DVI-D + HDMI, 12VDC In	Artikel-Nr. DMTX1030 12,1" DeltaToughMon Randloser Monitor IEC-60945, PCAP TouchScreen IP65/66 1.024x768 VGA,DP,HDMI

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



12,1" Einbaumonitor Front IP65 Typ 1



13,3" Einbaumonitor Front IP65 Typ 1



15" Einbaumonitor Full IP65 Typ 1

LCD Size	12,1"	13,3"	15"
Active Area	246 x 184 mm (H x V)	293,7 x 165,2 mm (H x V)	304 x 228 mm (H x V)
Pixel Pitch	-	-	-
Aspect Ratio	4:3	16:9	4:3
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	XGA (1.024x768)	1080p (1.920x1.080)	XGA (1.024x768)
Display Colors	16.7M	16.7M	16.7M
Brightness	500 cd/m²	350 cd/m²	1.000 cd/m²
Contrast Ratio	700:1	700:1	700:1
Response Time	25ms / 10ms (Tr / Tf)	14 ms / 11 ms (Tr / Tf)	8 ms / 12 ms (Tr / Tf)
Viewing Angle	160° / 160° (H / V)	178° / 178° (H / V)	160° / 160° (H / V)
ScanFrequency	-	-	-
Anti Reflection Glass	x	-	x
Strengthened Glass	7H Surface Hardness	7H Surface Hardness	7H Surface Hardness
Sunlight Readable	-	x	-
Gapless Optical Bonding	x	x	-
MTBF	50.000 hours	15.000 hours	30.000 hours
TouchScreen	Projected Capacitive 10-point Multi-touch	Projected Capacitive 10-point Multi-touch	Projected capacitive 10-Point
Keypad	5 Key	5 Key	2 Key
OSDMenu	-	-	-
Cooling System	-	-	-
Mounting System	75 x 75 mm VESA	100 x 100 mm VESA	100 x 100 mm VESA
Graphic Interface	VGA/CRT, HDMI, DisplayPort	VGA/CRT, HDMI, DisplayPort	HDMI
Interface COM			
Interface USB	USB-Touch USB	USB-Touch USB	USB-Touch USB
Video Input			
Video Output			
Audio	x	x	optional
Speakers	-	-	x
Operating System			
Operating System Support	Touch Panel Drivers: Windows, Linux, Mac, Android	Touch Panel Drivers: Windows, Linux, Mac, Android	Touch Panel Drivers: Windows, Linux, Mac, Android
Input Voltage Nominal	12VDC	12VDC	-
Input Voltage Min/Max	-	-	8 to 36VDC
Input Current	12W	12W	20W
Operating Temperature	-25°C to 75°C	-10 °C to 60 °C	-25 °C to 75 °C
Storage Temperature	-	-	-
Relative Humidity	10% to 90%	10% to 90%	10% to 90%
Protection	IP65 front / IP40 back	IP65 front / IP40 back	Full IP65
Certification	CE, FCC, RoHs	CE, FCC, RoHs	-
Dimensions	301 x 246 x 42,5 mm (L x W x H)	338,2 x 220,7 x 32,3 mm (L x W x H)	389,4 x 313,4 x 48 mm (L x W x H)
Weight	1,2 Kg	1,5 kg	3,0 Kg
Material	Silicone edge, ABS plastic Back housing	Silicone edge, ABS plastic Back housing	Aluminum Housing
Typ. Application	Industrial, Digital Signage, Outdoor	Industrial, Digital Signage, Outdoor	Industrial, Digital Signage, Outdoor

Bestellinformation	Artikel-Nr. DMXX3709-2 12,1" Einbaumonitor Front IP65 Type 1, Optical Bonding , LED Backlight, PCT, 500cd/m², 1.024x768, VGA+DVI-D+HDMI, 12VDC Input	Artikel-Nr. DMXX3711-1 13,3" Einbaumonitor Front IP65 Typ 1, Opt.Bonding, PCT, 350cd/m², 1.920x1.080, VGA+DP+HDMI, 12VDC In	Artikel-Nr. DMXX3782-1 15" Einbaumonitor Full IP65 Typ 1, 8-36VDC IN, LED Backlight, Resistive Touch, 1.000cd/m², 1.024x768, HDMI
--------------------	--	--	--

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



15" Einbaumonitor Front IP65 Typ 1



15" Einbaumonitor Front IP65 Typ 2



15" Industrial Touch Monitor Front IP65 Typ 1

LCD Size	15"	15"	15"
Active Area	304 x 228 mm	304 x 228 mm (H x V)	-
Pixel Pitch	-	-	-
Aspect Ratio	4:3	4:3	-
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	XGA (1.024x768)	XGA (1.024x768)	XGA (1.024x768)
Display Colors	16,7 M	16.7M	16.7M
Brightness	1.000 cd/m²	300 cd/m²	450cd/m²
Contrast Ratio	700:1	700:1	2.500:1
Response Time	8 ms / 12 ms (Tr / Tf)	8 ms / 12 ms (Tr / Tf)	-
Viewing Angle	160° / 160° (H / V)	160° / 160° (H / V)	176°/176° (H/V)
ScanFrequency	-	-	-
Anti Reflection Glass	x	-	-
Strengthened Glass	7H Surface Hardness, optically bonded	7H Surface Hardness	-
Sunlight Readable	-	x	-
Gapless Optical Bonding	-	x	-
MTBF	30.000 h	30.000 hours	-
TouchScreen	PCT	Projected Capacitive 10-point Multi-touch	5-wire resistive
Keypad	x	5 Key	-
OSDMenu	-	-	x
Cooling System	Fanless	-	-
Mounting System	100 x 100 mm VESA	100 x 100 mm VESA	Wall Mount, VESA, Stand
Graphic Interface	VGA/CRT, DVI, HDMI	VGA/CRT, HDMI, DisplayPort	1x VGA/CRT, 1x DVI
Interface COM	-	-	1x RS232
Interface USB	1x USB	USB-Touch USB	USB
Video Input	-	-	-
Video Output	-	-	-
Audio	1x PC-Audio	x	-
Speakers	-	-	-
Operating System	-	-	-
Operating System Support	Windows, Linux, Mac, Android	Touch Panel Drivers: Windows, Linux, Mac, Android	-
Input Voltage Nominal	-	12VDC	-
Input Voltage Min/Max	12VDC	-	12 to 24VDC
Input Current	15W	15W	60W
Operating Temperature	-10°C to 60°C	-10 °C to 60 °C	-5°C to 50°C
Storage Temperature	-	-	-20°C to 75°C
Relative Humidity	10% to 90%	10% to 90%	10% to 90%, non-condensing
Protection	IP65 front housing / IP40 back housing	IP65 front / IP40 back	IP65 front
Certification	CE, FCC	CE, FCC, RoHs	CE, FCC
Dimensions	362 x 286 x 49,8 mm (L x B x H)	359 x 298 x 45 mm (L x W x H)	384,37 x 309,95 x 51,2 mm
Weight	3 kg	4,1 kg	3,9 kg
Material	Aluminium	Silicone edge, ABS plastic Back housing	-
Typ. Application	Industrial, Marine, Digital Signage, Outdoor	Industrial, Digital Signage, Outdoor	Industrial, Outdoor
Bestellinformation	Artikel-Nr. DMXX3712-1 15" Einbaumonitor Front IP65 Typ 1, Optical Bonding, LED Backlight, PCT, 1.000cd/m², 1.024x768, VGA + DVI-D + HDMI, 12VDC In	Artikel-Nr. DMXX3713-1 15" Einbaumonitor Front IP65 Typ 2, Optical Bonding, PCT, 300cd/m², 1.024x768, VGA+DP+HDMI, 12VDC In	Artikel-Nr. DMXX5283-2 15.0" Industrial Touch Monitor Front IP65 Typ 1, XGA, 400cd/m², Contrast 2.500:1, VGA, DVI-D

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



15" IP65 Marine Monitor Typ 3, Front IP65



15,6" Einbaumonitor Front IP65 Typ 2



15,6" Einbaumonitor Front IP65 Typ 3

LCD Size	15"	15,6"	15,6"
Active Area	304.13 x 228.1mm	344,2 x 193,6 mm	344,2 x 193,6 mm (H x V)
Pixel Pitch	0.297 x 0.297 mm (H/V)	-	-
Aspect Ratio	-	16:9	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	XGA (1.024x768)	1080p (1.920x1.080)	1080p (1.920x1.080)
Display Colors	16.7M	16,7 M	262K
Brightness	1.600 cd/m²	1.000 cd/m²	250 cd/m²
Contrast Ratio	700:1	800:1	800:1
Response Time	8ms	15 ms / 15 ms (Tr / Tf)	15 ms / 15 ms (Tr / Tf)
Viewing Angle	160°/160° (H/V)	170° / 170° (H / V)	170° / 170° (H / V)
ScanFrequency	-	-	-
Anti Reflection Glass	-	x	-
Strengthened Glass	-	7H Surface Hardness, optically bonded	7H Surface Hardness
Sunlight Readable	x	-	x
Gapless Optical Bonding	x	-	-
MTBF	-	30.000 h	15.000 hours
TouchScreen	Projected Capacitive Multi-Touch	PCT	Projected Capacitive 10-point Multi-touch
Keypad	-	x	5 Key
OSDMenu	x	-	-
Cooling System	Fan	Fanless	-
Mounting System	Panel (Flush) mount Wall Mount, VESA	100 x 100 mm VESA	100 x 100 mm VESA
Graphic Interface	1x VGA/CRT, 1x DVI, 3x Composite/CVBS	VGA/CRT, DVI, HDMI	VGA/CRT, HDMI, DisplayPort
Interface COM	1x RS232	-	-
Interface USB	1x USB	1x USB	USB-Touch USB
Video Input	3x	-	-
Video Output	-	-	-
Audio	-	1x PC-Audio	x
Speakers	-	-	-
Operating System	-	-	-
Operating System Support	-	Windows, Linux, Mac, Android	Touch Panel Drivers: Windows, Linux, Mac, Android
Input Voltage Nominal	-	-	12VDC
Input Voltage Min/Max	9 to 36 VDC	12VDC	-
Input Current	23W	17W	13W
Operating Temperature	-20°C to 60°C	-10°C to 60°C	-10 °C to 60 °C
Storage Temperature	-20°C to 70°C	-	-
Relative Humidity	-	10% to 90%	10% to 90%
Protection	IP65 Facial Waterproof	IP65 front housing / IP40 back housing	IP65 front / IP40 back
Certification	CE, FCC	CE, FCC	CE, FCC, RoHS
Dimensions	389.4 x 331 x 57.1 (W x H x D)	400 x 260 x 40,1 mm (L x W x H)	389,3 x 246,8 x 33,3 mm (L x W x H)
Weight	4.1Kg	2,05 kg	3,4 kg
Material	Rugged Aluminum Alloy Chassis	Aluminium	Silicone edge, ABS plastic Back housing
Typ. Application	Industrial, Marine, Outdoor	Industrial, Marine, Digital Signage, Outdoor	Industrial, Digital Signage, Outdoor
Bestellinformation	Artikel-Nr. DMWX1104 15" IP65 Marine Monitor w/PCAP TouchScreen, IP65, 1.600nits, XGA resol., VGA, DVI, Video	Artikel-Nr. DMXX3719 15,6" Einbaumonitor Front IP65 Type 2, Optical Bonding, LED Backlight, PCT, 1.000cd/m2, 1.920x1.080, VGA + DVI-D + HDMI, 12VDC In	Artikel-Nr. DMXX3714-3 15,6" Einbaumonitor Front IP65 Typ 3, PCT, 250cd/m², 1.920x1.080, VGA + DVI-D + HDMI, 12VDC In

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



15.6" Factory Automation Touch Monitor, Front IP66



17" Einbaumonitor Front IP65 Typ 1



17" Industrial Touch Monitor Front IP65 Typ 1

LCD Size	15.6"	17"	17"
Active Area	-	337,9 x 270,4 mm (H x V)	-
Pixel Pitch	-	-	-
Aspect Ratio	16:9	5:4	-
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	WXGA (1.366x768)	SXGA (1.280x1.024)	SXGA (1.280x1.024)
Display Colors	16.7M	16.7M	-
Brightness	300 cd/m²	250 cd/m²	350 cd/m²
Contrast Ratio	500:1	1.000:1	800:1
Response Time	-	3,8 ms / 1,2 ms (Tr / Tf)	-
Viewing Angle	160°/170° (H/V)	170° / 160° (H / V)	140°/160° (H/V)
ScanFrequency	-	-	-
Anti Reflection Glass	-	-	-
Strengthened Glass	-	7H Surface Hardness	-
Sunlight Readable	-	x	-
Gapless Optical Bonding	-	x	-
MTBF	-	30.000 hours	-
TouchScreen	Ten points P-Cap (Projected Capacitive Touch)	Projected Capacitive 10-point Multi-touch	5-wire resistive
Keypad	-	5 Key	-
OSDMenu	(multilanguage)	-	-
Cooling System	Fan	-	Fanless
Mounting System	Wall Mount, VESA 100 x 100 mm VESA, Stand	100 x 100 mm VESA	Wall Mount, VESA, Stand
Graphic Interface	VGA/CRT, DVI, DisplayPort	VGA/CRT, HDMI, DisplayPort	1x VGA/CRT, 1x DVI
Interface COM	-	-	-
Interface USB	-	USB-Touch USB	-
Video Input	-	-	-
Video Output	-	-	-
Audio	-	x	-
Speakers	-	-	-
Operating System	-	-	-
Operating System Support	-	Touch Panel Drivers: Windows, Linux, Mac, Android	-
Input Voltage Nominal	-	12VDC	-
Input Voltage Min/Max	12 to 24VDC	-	12V to 24VDC
Input Current	-	15W	60W
Operating Temperature	-10°C to 60°C	-10 °C to 60 °C	-5°C to 50°C
Storage Temperature	-20°C to 75°C	-	-20°C to 75°C
Relative Humidity	10% ~ 90% relative humidity, non-condensing	10% to 90%	10% to 90%, non-condensing
Protection	IP66 front	IP65 front / IP40 back	IP65 front
Certification	(incl. EN61000-6-1/EN61000-6-2/EN61000-6-3/EN61000-6-4) CE, FCC	CE, FCC, RoHs	CE, FCC
Dimensions	417,4 x 312,4 x 51,75 mm	393 x 340 x 44 mm (L x W x H)	410,4 x 340,4 x 53,9 mm
Weight	5,48Kg	5,1 kg	4,8 kg
Material	metal housing with robust aluminum front zero bezel for harsh environment	Silicone edge, ABS plastic Back housing	-
Typ. Application	Industrial, Marine, Outdoor	Industrial, Digital Signage, Outdoor	Industrial, Outdoor
Bestellinformation	Artikel-Nr. DMXX5300 15.6" Factory Automation Touch Monitor IP66, LED, FHD, 300cd/m², 500 contrast, VGA, DVI, DP	Artikel-Nr. DMXX3716-1 17" Einbaumonitor Front IP65 Typ 1, Optical Bonding, PCT, 250cd/m², 1.280x1.024, VGA+DP+HDMI, 12VDC In	Artikel-Nr. DMXX5280-1 17.0" Industrial Touch Monitor Front IP65 Typ 1, SXGA, 350cd/m², Contrast 800:1, VGA, DVI-D

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



17" IP65 Marine Monitor Typ 1, Front IP65



17" IP65 Marine Monitor Typ 3, Front IP65



18.5" Factory Automation Touch Monitor, Front IP66

LCD Size	17"	17"	18.5"
Active Area	337.92 x 270.336 mm (H/V)	337.9 x 270.3mm	-
Pixel Pitch	0.264 x 0.264 mm (H/V)	0.264 (H) x 0.264 (V)	-
Aspect Ratio	-	-	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	SXGA (1.280x1.024)	SXGA (1.280x1.024)	WXGA (1.366x768)
Display Colors	16.7M	16.7M	16.7M
Brightness	1.000 cd/m²	1.600 cd/m²	300 cd/m²
Contrast Ratio	1.000:1	1.000:1	1.000:1
Response Time	5ms	5ms	-
Viewing Angle	160°/160° (H/V)	160°/160° (H/V)	160°/170° (H/V)
ScanFrequency	-	-	-
Anti Reflection Glass	Optional	-	-
Strengthened Glass	-	-	-
Sunlight Readable	x	x	-
Gapless Optical Bonding	x	x	-
MTBF	-	-	-
TouchScreen	Optional	Projected Capacitive Multi-Touch	Ten points P-Cap (Projected Capacitive Touch)
Keypad	-	-	-
OSDMenu	-	x	(multilanguage)
Cooling System	Fan	Fan	Fan
Mounting System	Panel (Flush) mount Wall Mount, VESA	Panel (Flush) mount Wall Mount, VESA	Wall Mount, VESA 100 x 100 mm VESA, Stand
Graphic Interface	2x VGA/CRT, 2x DVI, 3x Composite/CVBS	2x VGA/CRT, 2x DVI, 3x Composite/CVBS	VGA/CRT, DVI, DisplayPort
Interface COM	1x RS232	1x RS232	-
Interface USB	1x USB	1x USB	-
Video Input	-	3x	-
Video Output	-	-	-
Audio	-	-	-
Speakers	-	-	-
Operating System	-	-	-
Operating System Support	-	-	-
Input Voltage Nominal	-	-	-
Input Voltage Min/Max	9 to 36VDC	9 to 36 VDC	12 to 24VDC
Input Current	50W	38W	-
Operating Temperature	-10°C to 50°C	-10°C to 50°C	-10°C to 60°C
Storage Temperature	-	-20°C to 70°C	-20°C to 75°C
Relative Humidity	-	-	10% ~ 90% relative humidity, non-condensing
Protection	IP65	IP65 Facial Waterproof	IP66 front
Certification	CE, FCC	CE, FCC	(incl. EN61000-6-1/EN61000-6-2/EN61000-6-3/EN61000-6-4) CE, FCC
Dimensions	384 x 348.1 x 57.8 mm	413.4 x 371.9 x 58.2 mm (W x H x D)	490.8 x 320.6 x 50.65 mm
Weight	4.5kg	4.8kg	6.24Kg
Material	Aluminum	Rugged Aluminum Alloy Chassis	metal housing with robust aluminum front zero bezel for harsh environment
Typ. Application	Industrial, Marine, Outdoor	Industrial, Marine, Outdoor	Industrial, Marine, Outdoor

Bestellinformation

Artikel-Nr. DMWX1152

17" Marine Monitor w/anti-reflection glass,
IP65,LED backlight,1.000 nits, SXGA resolution,
w/adapter

Artikel-Nr. DMWX1153

17" Marine Monitor w/USB TouchScreen Resistive,
IP65,LED backlight,1.000 nits, SXGA resolution,
w/adapter

Artikel-Nr. DMWX1154

17" IP65 Marine Monitor w/PCAP TouchScreen,
IP65, 1.600nits, SXGA resol., VGA, DVI, Video

Artikel-Nr. DMXX5301

18.5" Factory Automation Touch Monitor IP66,
LED, WXGA, 300cd/m², 1.000 contrast, VGA, DVI,
DP

Bitte laden Sie sich bei Bedarf [hier](#) eine aktualisierte Fassung dieses Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.

Selection Guide Marine IP6x High-Performance Monitore



19" Einbaumonitor Front IP65 Typ 1



19" IP65 Marine Monitor Typ 3, Front IP65



21,5" Einbaumonitor Front IP65 Typ 1

LCD Size	19"	19"	21,5"
Active Area	379,3 x 304,1 mm (H x V)	376.3 x 301.1mm	477 x 268 mm
Pixel Pitch	-	0.294 x 0.294 (HxV)	-
Aspect Ratio	5:4	-	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	SXGA (1.280x1.024)	SXGA (1.280x1.024)	1080p (1.920x1.080)
Display Colors	16.7M	16.7M	16,7 M
Brightness	250 cd/m²	1.600 cd/m²	1.000 cd/m²
Contrast Ratio	1.000:1	1.000:1	1.000:1
Response Time	1,5 ms / 3,5 ms (Tr / Tf)	5ms	7 ms / 7 ms (Tr / Tf)
Viewing Angle	170° / 160° (H / V)	170°/160° (H/V)	178° / 178° (H / V)
ScanFrequency	-	-	-
Anti Reflection Glass	-	-	x
Strengthened Glass	7H Surface Hardness	-	7H Surface Hardness, optically bonded
Sunlight Readable	x	x	-
Gapless Optical Bonding	x	x	-
MTBF	40.000 hours	-	100.000 h
TouchScreen	Projected Capacitive 10-point Multi-touch	Projected Capacitive Multi-Touch	PCT
Keypad	5 Key	-	x
OSDMenu	-	x	-
Cooling System	-	Fan	Fanless
Mounting System	100 x 100 mm VESA	Panel (Flush) mount Wall Mount, VESA	100 x 100 mm VESA
Graphic Interface	VGA/CRT, HDMI, DisplayPort	2x VGA/CRT, 2x DVI, 3x Composite/CVBS	VGA/CRT, DVI, HDMI
Interface COM	-	1x RS232	-
Interface USB	USB-Touch USB	1x USB	1x USB
Video Input	-	3x	-
Video Output	-	-	-
Audio	x	-	1x PC-Audio
Speakers	-	-	2x 2W
Operating System	-	-	-
Operating System Support	Touch Panel Drivers: Windows, Linux, Mac, Android	-	Windows, Linux, Mac, Android
Input Voltage Nominal	12VDC	-	-
Input Voltage Min/Max	-	9 to 36 VDC	12VDC
Input Current	25W	42W	28W
Operating Temperature	-10 °C to 60 °C	-10°C to 50°C	-10°C to 60°C
Storage Temperature	-	-20°C to 70°C	-
Relative Humidity	10% to 90%	-	10% to 90%
Protection	IP65 front / IP40 back	IP65 Facial Waterproof	IP65 front housing / IP40 back housing
Certification	CE, FCC, RoHs	CE, FCC	CE, FCC
Dimensions	431,5 x 364,5 x 43 mm (L x W x H)	463 x 411.1 x 56.9 mm (W x H x D)	527,9 x 328 x 51,1 mm (L x W x H)
Weight	6,2 kg	5.5Kg	5 kg
Material	Silicone edge, ABS plastic Back housing	Rugged Aluminum Alloy Chassis	Aluminum
Typ. Application	Industrial, Digital Signage, Outdoor	Industrial, Marine, Outdoor	Industrial, Marine, Digital Signage, Outdoor

Bestellinformation	Artikel-Nr. DMXX3718-1 19" Einbaumonitor Front IP65 Typ 1, Optical Bonding, PCT, 250cd/m², 1.280x1.024, VGA+DP+HDMI, 12VDC In	Artikel-Nr. DMWX1205 19" IP65 Marine Monitor w/PCAP TouchScreen, IP65, 1.600nits, SXGA resol., VGA, DVI, Video	Artikel-Nr. DMXX3723 21,5" Einbaumonitor Front IP65 Typ 1, Optical Bonding, LED Backlight, PCT, 1.000cd/m², 1.920x1.080, VGA + DVI-D + HDMI, 12VDC In
--------------------	--	---	--

PDF Online Selection Guide
Stand vom 18.05.2024 - 23:42:21

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.



21,5" Einbaumonitor Front IP65 Typ 2



21,5" IP65 Marine Monitor Typ 1, Front IP65



21,5" Factory Automation Touch Monitor, Front IP66

LCD Size	21,5"	21,5"	21,5"
Active Area	477,7 x 269,1 mm	476.64 x 268.11 mm (H/V)	-
Pixel Pitch	-	0.248 x 0.248 mm (H/V)	-
Aspect Ratio	16:9		16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	1080p (1.920x1.080)	1080p (1.920x1.080)	1080p (1.920x1.080)
Display Colors	16.7M	16.7M	16.7M
Brightness	250 cd/m²	1.000 cd/m²	300 cd/m²
Contrast Ratio	1.000:1	1.000:1	5.000:1
Response Time	1,5ms / 3,5ms (Tr / Tf)	5ms	-
Viewing Angle	170° / 160° (H / V)	170°/160° (H/V)	178°/178° (H/V)
ScanFrequency	-	-	-
Anti Reflection Glass	x	Optional	-
Strengthened Glass	7H Surface Hardness, optically bonded	-	-
Sunlight Readable	-	x	-
Gapless Optical Bonding	x	x	-
MTBF	40.000 hours	-	-
TouchScreen	Projected Capacitive 10-point Multi-touch	Optional	Ten points P-Cap (Projected Capacitive Touch)
Keypad	5 Key	-	-
OSDMenu	-	-	(multilanguage)
Cooling System	-	Fan	Fan
Mounting System	100 x 100 mm VESA, Stand	Panel (Flush) mount Wall Mount, VESA	Wall Mount, VESA 100 x 100mm VESA, Stand
Graphic Interface	VGA/CRT, HDMI, DisplayPort	2x VGA/CRT, 2x DVI, 3x Composite/CVBS	VGA/CRT, DVI, DisplayPort
Interface COM		1x RS232	
Interface USB	USB-Touch USB	1x USB	-
Video Input		-	
Video Output		-	
Audio	x	-	
Speakers	-	-	
Operating System			
Operating System Support	Touch Panel Drivers: Windows, Linux, Mac, Android		
Input Voltage Nominal	12VDC	-	-
Input Voltage Min/Max	-	9 to 36VDC	12 to 24VDC
Input Current	22W	26W	-
Operating Temperature	-10 °C to 60 °C	-10°C to 50°C	-10°C to 60°C
Storage Temperature	-	-	-20°C to 75°C
Relative Humidity	10% to 90%	-	10% ~ 90% relative humidity, non-condensing
Protection	IP65 front / IP40 back	IP65	IP66 front
Certification	CE, FCC	CE, FCC, IEC 60945	(incl. EN61000-6-1/EN61000-6-2/EN61000-6-3/EN61000-6-4) CE, FCC
Dimensions	532 x 338 x 46 mm (L x W x H)	528.8 x 345.2 x 56.4 mm	562.4 x 382.4 x 50.85 mm
Weight	7,3 Kg	7.87 kg	7.87Kg
Material	Rubber front case and plastic back case	Aluminum	metal housing with robust aluminum front zero bezel for harsh environment
Typ. Application	Industrial, Digital Signage, Outdoor	Industrial, Marine, Outdoor	Industrial, Marine, Outdoor

Bestellinformation	Artikel-Nr. DMXX3722-1 21,5" Einbaumonitor Front IP65 Typ 2, Opt. Bonding, PCT,250cd/m²,1.920x1.080, VGA+DP+HDMI, 12VDC In	Artikel-Nr. DMWX1252 21.5" Marine Monitor w/anti-reflection glass, IP65, LED backlight, 1.000 nits, FHD resolution, w/adapter Artikel-Nr. DMWX1253 21.5" Marine Monitor w/USB TouchScreen Resistive, IP65, LED backlight, 1.000 nits, FHD resolution w/adpater	Artikel-Nr. DMXX5302 21.5" Factory Automation Touch Monitor IP66, LED, FHD, 300cd/m², 5.000 contrast, VGA, DVI, DP
--------------------	---	---	---

Bitte laden Sie sich bei Bedarf [hier](#) eine aktualisierte Fassung dieses Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.

Selection Guide Marine IP6x High-Performance Monitore



24" Einbaumonitor Front IP65 Typ 1



24" IP65 Marine Monitor Typ 3, Front IP65



27" Einbaumonitor Front IP65 Typ 1

LCD Size	24"	24"	27"
Active Area	531,3 x 298,8 mm	531.36 x 298.89 mm	597,6 x 336,2 mm
Pixel Pitch	-	0.276 x 0.276 (H x V)	-
Aspect Ratio	16:9	-	16:9
Display Backlight	LED Backlight	LED Backlight	LED Backlight
Display Resolution	1080p (1.920x1.080)	1080p (1.920x1.080)	1080p (1.920x1.080)
Display Colors	16.7M	16.7M	16.7M
Brightness	500 cd/m²	1.000 cd/m²	350 cd/m²
Contrast Ratio	3.000:1	3.000:1	3.000:1
Response Time	3,5 ms / 1,5 ms (Tr / Tf)	25ms	7 ms / 5 ms (Tr / Tf)
Viewing Angle	170° / 160° (H / V)	178°/178° (H/V)	178° / 178° (H / V)
ScanFrequency	-	-	-
Anti Reflection Glass	x	-	x
Strengthened Glass	7H Surface Hardness	-	7H Surface Hardness
Sunlight Readable	-	x	-
Gapless Optical Bonding	x	x	-
MTBF	20.000 hours	-	30.000 hours
TouchScreen	Projected Capacitive 10-point Multi-touch	Projected Capacitive Multi-Touch	Projected Capacitive 10-point Multi-touch
Keypad	-	-	-
OSDMenu	-	x	-
Cooling System	-	Fan	-
Mounting System	100 x 100 mm VESA, Stand	Panel (Flush) mount Wall Mount, VESA	VESA, Stand
Graphic Interface	VGA/CRT, HDMI, DisplayPort	2x VGA/CRT, 2x DVI, 3x Composite/CVBS	VGA/CRT, DVI, HDMI
Interface COM	-	1x RS232	-
Interface USB	USB-Touch USB	-	USB-Touch USB
Video Input	-	3x	-
Video Output	-	-	-
Audio	x	-	x
Speakers	x	-	-
Operating System	-	-	-
Operating System Support	Touch Panel Drivers: Windows, Linux, Mac, Android	-	Touch Panel Drivers: Windows, Linux, Mac, Android
Input Voltage Nominal	12VDC	-	12VDC
Input Voltage Min/Max	-	9 to 36 VDC	-
Input Current	20W	50W	20W
Operating Temperature	-10 °C to 60 °C	-10°C to 50°C	-10 °C to 60 °C
Storage Temperature	-	-20°C to 70°C	-
Relative Humidity	10% to 90%	-	10% to 90%
Protection	IP65 front / IP40 back	IP65 facial waterproof	IP65 front / IP40 back
Certification	CE, FCC	CE, FCC, IEC 60945	CE, FCC
Dimensions	579,4 x 347 x 41,5 mm (L x W x H)	601.68 x 423.3 x 57.7 mm (W x H x D)	663 x 405 x 46 mm (L x W x H)
Weight	6,8 kg	7.8 kg	7,5 kg
Material	Rubber front, plastic ABS back case	Rugged Aluminum Alloy Chassis	Rubber front, plastic ABS back case
Typ. Application	Industrial, Marine, Digital Signage, Outdoor	Industrial, Marine, Outdoor	Industrial, Marine, Digital Signage, Outdoor

Bestellinformation	Artikel-Nr. DMXX3736 24" Einbaumonitor Front IP65 Typ 1, Opt. Bonding, PCT, 500cd/m², 1.920x1.080, VGA+DP+HDMI, 12VDC In	Artikel-Nr. DMWX1304-1 24" IP65 Marine Monitor w/ PCAP Touch Screen, IP65, 1.000 nits, FHD resol., VGA, DVI, Video	Artikel-Nr. DMXX3725 27" Einbaumonitor Front IP65 Type 1, Optical Bonding, LED Backlight, PCT, 300cd/m², 1.920x1.080, VGA + DVI-D + HDMI Artikel-Nr. DMXX3725-1 27" Einbaumonitor Front IP65 Typ 2, Optical Bonding, LED, PCT, 300cd/m², 1.920x1.080, VGA+DP+HDMI
--------------------	---	---	--

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

38 Artikel aus dem Bereich
Marine IP6x Monitore
wurden für das PDF ausgewählt.

Selection Guide Marine IP6x High-Performance Monitore



31,5" Einbaumonitor Front IP65 Typ 1

43" Einbaumonitor Front IP65 Type 2

LCD Size	31,5"	43"
Active Area	698,4 x 392,9 mm	940,9 x 529,2 mm
Pixel Pitch	-	-
Aspect Ratio	16:9	16:9
Display Backlight	LED Backlight	LED Backlight
Display Resolution	1080p (1.920x1.080)	2160p (3.840x2.160)
Display Colors	16,7 M	10,7 B
Brightness	1.000 cd/m²	1.000 cd/m²
Contrast Ratio	1.200:1	4.000:1
Response Time	8 ms / 8 ms (Tr / Tf)	8 ms / 8 ms (Tr / Tf)
Viewing Angle	178° / 178° (H / V)	179° / 179° (H / V)
ScanFrequency	-	-
Anti Reflection Glass	x	x
Strengthened Glass	7H Surface Hardness, optically bonded	7H Surface Hardness, optically bonded
Sunlight Readable	-	-
Gapless Optical Bonding	-	-
MTBF	100.000 h	100.000 h
TouchScreen	PCT	PCT 10-point Multi Touch
Keypad	x	x
OSDMenu	-	-
Cooling System	Fanless	Fanless
Mounting System	400 x 300 mm VESA	400 x 300 mm VESA
Graphic Interface	VGA/CRT, DVI, HDMI	2 x HDMI, DisplayPort
Interface COM		1x 1 for controller
Interface USB	1x USB	1 for Touch USB
Video Input		
Video Output		
Audio	1x PC-Audio	1x Headphone output
Speakers	2x 2W	2x 3W
Operating System		
Operating System Support	Windows, Linux, Mac, Android	Windows, Linux, Mac, Android
Input Voltage Nominal	24VDC	-
Input Voltage Min/Max	100 to 240VACDC active switching	100 to 240VACDC active switching
Input Current	65W	137W
Operating Temperature	-10°C to 60°C	-10°C to 60°C
Storage Temperature	-	-
Relative Humidity	10% to 90%	10% to 90%
Protection	IP65 front housing / IP40 back housing	IP65 front housing / IP40 back housing
Certification	CE, FCC	CE, FCC
Dimensions	757 x 464 x 59,4 mm (L x W x H)	1.020 x 608,5 x 63,5 mm (L x W x H)
Weight	12 kg	23 kg
Material	Aluminum	Aluminium
Typ. Application	Industrial, Marine, Digital Signage, Outdoor	Industrial, Marine, Digital Signage, Outdoor
Bestellinformation	Artikel-Nr. DMXX3733-1 31,5" Einbaumonitor Front IP65 Typ 1, Optical Bonding, LED Backlight, PCT, 1.000cd/m², 1.920x1.080, VGA + DVI-D + HDMI, 24VDC In	Artikel-Nr. DMXX3741-1 43" Einbaumonitor Front IP65 Type 2, Optical Bonded, PCT, 1.000cd/m², 3.840x2.160, USB + DP + HDMI + RJ45

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

<https://www.delta-components.de>

<https://www.automotive-computing.com>