

Selection Guide

ANPR / LPR Cameras

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

www.delta-components.de

www.automotive-computing.com

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

3 Artikel aus dem Bereich
ANPR / LPR Cameras
wurden für das PDF ausgewählt.

Selection Guide ANPR / LPR Cameras



Short Range LPR Camera NCr-304-VHR



Mid Range LPR Camera NCr-305-VHR



IP Mid Range LPR Camera
NCr-662-VHA

LCD Size			
Image Sensor	1/3" 3MP True WDR progressive scan CMOS sensor	1/3" 3MP True WDR progressive scan CMOS sensor	1/1,8" 6MP True WDR progressive scan CMOS sensor
Minimal Lux	B/W 0 lux/Color 0.1 lux	B/W 0 lux/Color 0.1 lux	B/W 0 lux / Color 0.1 lux
Lens	Motorized (3-10mm, F1.4) lens	Motorized (9-22mm, F1.5) lens	Motorized 12-40 mm Lens, F2.1
IrisType	P-Iris	P-Iris	P-Iris
Day + Night	x	x	x
IR Distance	Effective up to 30M	Effective up to 50M	Effective up to 40M
IR Control	x	x	x
ICR	x	x	x
WDR	x	x	x
SD	-	-	1x microSD card slot
Removeable Storage	-	-	-
Internal Storage			
Graphic Interface	-	-	-
Interface COM			
Interface USB	-	-	-
Interface LAN	RJ45 10/100/1000 BASE-T, IEEE 802.3at (PoE+) PoE	RJ45 10/100/1000 BASE-T, IEEE 802.3at (PoE+) PoE	RJ45 10/100/1000 BASE-T, IEEE 802.3at (PoE+) PoE
Interface IO	1x DI, 1x DO GPIO	1x DI, 1x DO GPIO	1x DI, 1x DO GPIO
Resolution	2048x1536 @30 fps 1920x1080 @60 fps 1280x720 @30 fps 720x576 @30 fps 720x480 @30 fps 640x480 @30 fps 320x240 @30 fps	2.048 x 1.536 @30 fps 1.920 x 1.080 @60 fps 1.280 x 720 @30 fps 720 x 576 @30 fps 720 x 480 @30 fps 640 x 480 @30 fps 320 x 240 @30 fps	1.080P @ 30fps
Processing	VBR/CBR	VBR/CBR	VBR / CVBR
Codec	H.264/M-JPEG	H.264/M-JPEG	H.264 / M-JPEG
Performance	Triple streaming	Triple streaming	Triple streaming
Audio	Line-In, Line-Out	Line-In, Line-Out	Line-In, Line-Out, 2x 3,5 mm phone jack
Input Voltage Nominal	DC12V / AC 24V terminal block	DC12V / AC 24V terminal block	12VDC / 24VAC terminal block
Input Current	14.3W max	14.3W max	18W max.
Battery	-	-	-
Operating Temperature	-40°C to 60°C	-40°C to 60°C	-40°C to 60°C
Storage Temperature	-	-	-
Relative Humidity	90% RH, no condensation	90% RH, no condensation	90% RH, no condensation
Protection	IK10, IP66 / IP67	IK10, IP66 / IP67	IK10, IP66 / IP67
Certification	CE, FCC	CE, FCC	CE, FCC
Dimensions	406.2 x 161 x 263.3mm (D x W x H)	406.2 x 161 x 263.3mm (D x W x H)	317,23 x 161 x 263,3 mm (D x W x H)
Weight	2.005g	2.005g	3 kg
Typ. Application	-	-	Outdoor
Bestellinformation	Artikel-Nr. VKIX2024 Short Range LPR Camera NCr-304-VHR, -40°C to 60°C 1080P@60fps, H.264/ M-JPEG, true WDR, Smart IR, 3MP	Artikel-Nr. VKIX2035 Mid Range LPR Camera NCr-305-VHR, -40°C to 60°C 1080P@60fps, H.264/M-JPEG, Smart LPR Modes, TrueWDR	Artikel-Nr. VKIX2037 IP Mid Range LPR Camera NCr-662-VHA, -40°C to 60°C, 6MP 1.080P@30fps, H.264/M-JPEG, trueWDR, MicroSD, P-Iris

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

<https://www.delta-components.de>

<https://www.automotive-computing.com>